


## 产品型号IPC-4600



## 产品特性

- ▶ Intel® Kaby Lake-S/Skylake-S Series CPU to maximize performance
- ▶ 2 DDR4 2133/2400MHz UDIMMs slots up to 32 GB memory
- ▶ Supports VGA, HDMI and dual Intel® GbE LAN
- ▶ Supports 4 SATA-3.0, 4 USB 3.0, 5 USB 2.0
- ▶ 6 COM ports for flexible applications
- ▶ Supports 1 PCIe x 16, 1 PCIe x4 and 5 PCI Slots
- ▶ ATX Power



 **技术参数**


■ 产品型号		IPC-4600
系统	CPU	7th/6th Gen Intel® Desktop Kaby Lake/Skylake i7/i5/i3/ Pentium® /Celeron® Series Processor, Max 65W
	芯片组	Intel® H110 Express Chipset
	系统内存	2 * DDR4 UDIMM slots / Dual-Channel DDR4 memory up to 2133/2400MHz /Max 32GB
	扩展	1 * PCIe x16 slot (PCIe1) 1 * PCIe x4 signal (PCIe2) 5 * PCI slots (PCI1, PCI2, PCI3, PCI4, PCI5)
	GPU&显卡	1*VGA up to 1920 x 1200 @60Hz 1*HDMI up to 4096 x 2160 @24Hz
	音频	Realtek® ALC887 High Definition Audio codec (Co-lay ALC888S) 1 * Line-In jack 1 * Line-Out jack 1 * Mic-In jack
	以太网	1 x Intel® I219-LM GbE LAN PHY 1 x Intel® I211-AT GbE LAN
	存储	4 x SATA 3.0
	PS/2	1 x PS/2 port by Y-cable for keyboard and mouse
	USB接口	4 x USB 3.0 (4 x rear) 5 x USB 2.0 (2 x rear) 3 x internal with one Vertical Type-A)
	串口接口	6 x COM ports (2 x rear, 4 x Internal) COM1: RS-232/422/485, 0V/5V/12V, Auto-flow Control COM2~6: RS-232, COM2: 0V/5V/12V
	控制开关	1 * Power switch
	电源要求	ATX-Power 24P, 12V-8P
	GPIO	8-bits (4 x GPI; 4 x GPO), 5V

	操作系统	Windows 10 (64-bit) Windows 7 (32/64-bit) (Intel® Skylake-S Series CPU Only) Windows 8.1 (64-bit) (Intel® Skylake-S Series CPU Only) Linux Fedora 23 (by request) Linux Ubuntu 16.04 (by request)
结构	构造	SGCC箱体
	颜色	银色
	安装方式	上架式安装
	包装尺寸	483x480x177mm
	净重	15KG
环境	工作温度	-10 ~ 60°C
	存储温度	-20 ~ 80°C
	存储湿度	10 ~ 90%, non-condensing
	振动	5grms/5~500Hz/随机/工作状态(SSD); 1grms/5~500Hz/随机/工作状态(HDD)
	冲击	50g峰值加速度(持续11ms)(SSD); 20g峰值加速度(持续11ms)(HDD)
	EMC/认证	质量管理体系符合GB/T19001-2016/ISO9001:2015/CE/CCC/FCC

## ■ 订购信息

IPC-4600	IPC-4600/S001	Intel® Core i3-6100/i3-6100TE /2*DDR4/1*PCIe x16/1*PCIe x4/5*PCI/ 1*HDMI/1*VGA/2*LAN/4*USB3.0/5*USB2.0/ATX 24pin POWER
	IPC-4600/S002	Intel® Core i5-6500/i5-6500TE/2*DDR4/1*PCIe x16/1*PCIe x4/5*PCI/ 1*HDMI/1*VGA/2*LAN/4*USB3.0/5*USB2.0/ATX 24pin POWER
	IPC-4600/S003	Intel® Core i7-6700/i7-6700TE/2*DDR4/1*PCIe x16/1*PCIe x4/5*PCI/1*HDMI/1*VGA/2*LAN/4*USB3.0/5*USB2.0/ATX 24pin POWER
供电	PA-300ATX	ADC110/220V宽范围，并且在DC90V~DC264V范围内正常工作
	PA-450ATX	ADC110/220V宽范围，并且在DC90V~DC264V范围内正常工作
	PA-550W冗余	AC INPUT/输入/输入：100-240V~7-3.5A 60/50Hz DC INPUT/输入/输入：240V=3.5A(仅限中国地区使用/Only in China)

## 外形尺寸



## 北京总部

公司电话: +86(0)10 -82331878/82331875

服务热线: 400-800-1871

办公地址: 北京市海淀区双清路3号鸿运大厦1层31078室

工厂地址: 河北省廊坊市三河市燕郊开发区留山大街

创智谷产业园-1#地块-一期-4#-2-101

了解更多信息: [www.ipccore.com](http://www.ipccore.com) ,或发送邮件到: [ipc@ipccore.com](mailto:ipc@ipccore.com)规格细节如有变更, 恕不另行通知  
东方松柏科技(北京) 有限公司, 版权所有©2018